DRAMA FS-LED 900
350W LED Followspot

TIMES SQUARE LIGHTING

5 Holt Drive,
Stony Point, NY 10980
845-947-3034
www.tslight.com

The Drama FS-LED 900 is an extremely powerful follow spot LED fixture. Faders and buttons are located on the included DMX controller. The unit has a color wheel that produces a red, green, yellow, blue, orange and white spotlight. It features a CTO wheel, used both for adjusting color temperature and the color hue of each primary and secondary color. The diameter of the spot can be easily adjusted with the unit's built-in iris, great for long throw highlighting of small objects on stage. The Drama FS-LED 900 has a fader for controlling the smooth dimmer. The unit ships with the stand and is compact, allowing for easy transport and use in cramped spaces.

Specifications

- **DMX CONNECTORS:** 3 and 5-pin XLR Connectors In/Out
- **POWER CONNECTIONS:** Panel mount Power Con type in/out connection (Nema 5-15 to Blue power con type cable included)
- **THERMAL:** Maximum ambient temperature 40° C; Maximum surface temperature 60° C
- **DISPLAY:** Digital
- **FASTENING SYSTEM:** Mounting joke for stand (black diecast aluminum stand included)
- **ZOOM ANGLE:** 8° to 13°
- **COLOR:** 5 Color Wheel with Fader and DMX Control
- **CTO:** 3 CTO Filters 4353k, 4997k, and 5062k with Fader and DMX Control
- **FOCUS:** Mechanical Focus with Fader and DMX Control
- **IRIS:** Mechanical Iris with Fader and DMX Control
- **DIMMER:** Electronic Dimmer with Fader and DMX Control
- **SHUTTER:** Electronic Shutter with DMX Control only
- **LED TYPE:** 350W COB LED
- **CRI:** 91.1>
- **CCT:** 5080K on Open
- **LED LIFETIME:** 60,000 to 100,000 hours
- **POWER CONSUMPTION:** Universal 100 - 240V 50/60 Hz
- **BALLAST:** Electronic
- **PROTOCOL:** DMX 512
- **DMX CHANNELS:** 7 Channel Dimmer, Strobe, Iris, Color, CTO, Focus, Zoom
- **OPERATING MODE:** Rail Mounted Controller (Included)

Photometrics

FIXTURE OPEN

CCT	14671K
CRI	80
TM-30(Rf)	70
TM-30(Rg)	95

CTO 1

CCT	10256K
CRI	81
TM-30(Rf)	71
TM-30(Rg)	96

CTO 2

CCT	6218K
CRI	76
TM-30(Rf)	72
TM-30(Rg)	94

CTO 3

CCT	3901K
CRI	73
TM-30(Rf)	70
TM-30(Rg)	95

Physical Size

- **SIZE:** 10.33" x 34.5" x 13.5"
- **WEIGHT:** 34.40 lbs.