

Job Name: Fixture Type: Qty:



PRISMSource Inground 3,6,7,12



Industry standard inground fittings with an IP rating of 67 combined with drive over load bearings allows the dramatic effects of PRISMSource to be introduced to landscape illumination.

Technical Specifications:

<p>Max. input current: Maximum Power Consumption: Compatible Power Supplies: Compatible Power Supplies for single color variants: Optical System: LED Device: Warm White LEDs (WW): Cool White LEDs (CW): Typical Lumen Maintenance: Led Life Expectancy: Construction: top flange: housing: mounting sleeve: cover:</p> <p>Weight: Ingress Protection: Power/Data Plug: LED Color Variants:</p>	<p>PRISMSource Inground 3 350 mA 4.2 Watts PRISMPower 36, 72, 144, 360, 16x16</p> <p>PRISMPower SmartWhite 36,144 6°, 15°, 25° 1 Watt Luxeon 3300 K 6500 K 70% @ 50,000 hours minimum 50,000 hours stainless steel hardened aluminium plastic tempered glass</p> <p>1.1 lbs IP 67 RJ45 RGB, R, G, B, A, CW, WW</p>	<p>PRISMSource Inground 6 350 mA 8.4 Watts PRISMPower 36, 72, 144, 360, 16x16</p> <p>PRISMPower SmartWhite 36,144 6°, 25° 1 Watt Luxeon 3300 K 6500 K 70% @ 50,000 hours minimum 50,000 hours stainless steel hardened aluminium plastic tempered glass</p> <p>2.6 lbs IP 67 RJ45 RGB, RGBCW, RGBWW,R, G, B, A, CW, WW</p>
<p>Max. input current: Maximum Power Consumption: Compatible Power Supplies: Compatible Power Supplies for single color variants: Optical System: LED Device: Warm White LEDs (WW): Cool White LEDs (CW): Typical Lumen Maintenance: Led Life Expectancy: Construction: top flange: housing: mounting sleeve: cover:</p> <p>Weight: Ingress Protection: Power/Data Plug: LED Color Variants:</p>	<p>PRISMSource Inground 7 350 mA 9.6 Watts PRISMPower 36, 72, 144, 360, 16x16</p> <p>PRISMPower SmartWhite 36,144 6°, 25° 1 Watt Luxeon 3300 K 6500 K 70% @ 50,000 hours minimum 50,000 hours stainless steel hardened aluminium plastic tempered glass</p> <p>2.6 lbs IP 67 RJ45 RGBCW, RGBWW, R, G, B, A, CW, WW</p>	<p>PRISMSource Inground 12 350 mA 13.6 Watts PRISMPower 36, 72, 144, 360</p> <p>PRISMPower SmartWhite 36,144 6°, 15°, 25°, 38° 1 Watt Luxeon 3300 K 6500 K 70% @ 50,000 hours minimum 50,000 hours stainless steel hardened aluminium plastic tempered glass</p> <p>4.4 lbs IP 67 RJ45 RGB, RGBWW, RGBCW, R, G, B, A, CW, WW, SW</p>

