

# ASPIRE WW IP



5 Holt Drive,  
Stony Point, NY 10980  
845-947-3034  
info@tslight.com

The IP65 rated ASPIRE WW IP™ ellipsoidal features a High Power 130W Warm White >91CRI 3,000K LED engine producing 10,000+ total lumens, 19°, 26°, 36°, and 50° interchangeable lens options (sold separately), (4) blade manual framing shutters, supports B size metal gobos (gobo holder not included) and an optional IP65 rated DMX controlled dual gobo rotator (sold separately), manual focus, DMX controlled electronic strobe, 16bit dimming and selectable dimming curve modes, flicker free operation for TV and FILM, adjustable refresh frequency and gamma brightness, IP rated 5pin DMX and powerCON TRUE1 in/out connections, (4) button LCD control display panel, an integrated rigging yoke, quiet fan cooling, and a multi-voltage universal auto switching power supply (100-240v).

## Features

- IP65 Rated High Power Ellipsoidal
- 130W Warm White 3,000K LED Engine
- > 91CRI and 10,000+ Total Lumens Output
- 19°, 26°, 36°, 50° Lens Options (sold separately)
- Supports B Size Metal Gobos (gobo holder not included)
- IP65 DMX Controlled Dual Gobo Rotator (sold separately)
- (4) Blade Manual Framing Shutters
- DMX Controlled Electronic Strobe and 16bit Dimming Selectable Selectable Dimming Curve Modes
- Flicker Free Operation for TV and FILM
- Adjustable Refresh Frequency and Gamma Brightness
- Quiet Fan Cooling

## Optional Accessories

- PHD019** Profile High Definition Lens 19°
- PHD126** Profile High Definition Lens 26°
- PHD236** Profile High Definition Lens 36°
- PHD350** Profile High Definition Lens 50°

## Source

- High Power 130W Warm White LED Engine
- 50,000 Hour Average LED Life\*
- LED Life may vary depending on several factors including but not limited to:

Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control and Dimming.

## Photometric Data

- > 91CRI | 10,000+ Total Lumens

## Gobos

- Supports "B" Size Metal Gobos (gobo holder not included)
- IP65 Rated DMX Controlled Dual Gobo Rotator (sold separately)

## Size / Weight

- Length: 29.6"
- Width: 13.9"
- Vertical Height: 18.9"
- Weight: 24 lbs.

## APPROVALS / RATINGS

- CE
- cETLus
- IP65

## Effects

- Electronic Strobe and 16bit Dimming
- Selectable Dimming Curve Modes

## Controls / Connections

- 3 DMX Channel Modes (3 / 6 / 8)
- Adjustable Refresh Rates
- Adjustable Gamma Brightness
- 4 Button Control Panel / LED Menu Display
- IP Rated 5pin DMX In/Out / powerCON TRUE1 In/Out

## Electrical / Thermal

- Quiet Fan Cooling
- AC 100-240V - 50/60Hz
- 170W Max Power Consumption
- 14° to 113°F (-10° to 45°C)

## Photometric Data

### 19° LENS ZOOM IN @ FULL ON | 3,159K

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
4,005	641	327	160	71	40

### 19° LENS ZOOM OUT @ FULL ON | 3,170K

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
3,560	570	291	142	63	36

### 26° LENS ZOOM IN @ FULL ON | 3,138K

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
2,721	435	222	109	48	27

### 26° LENS ZOOM OUT @ FULL ON | 3,163K

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
2,538	406	207	102	45	25

### 36° LENS ZOOM IN @ FULL ON | 3,154K

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
1,621	379	167	97	46	29

### 36° LENS ZOOM OUT @ FULL ON | 3,172K

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
1,621	379	167	97	46	29

### 50° LENS ZOOM IN @ FULL ON | 3,146K

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
1,621	379	167	97	46	29

### 50° LENS ZOOM OUT @ FULL ON | 3,160K

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
1,621	379	167	97	46	29

## Patterns

For standard and custom patterns please see the pattern specification sheet. For a complete list, please contact a Times Square Lighting representative.

View Patterns: <http://tsq.li/2bMBz3l>

