

Commercial UV Purification System



5 Holt Drive,
Stony Point, NY 10980
845-947-3034
www.tslight.com

Information

- **Lamp Cycle:** 18,000 Hours

Operation

The continuously operation, germicidal coil cleaner uses high intensity UV-C to irradiate and kill bacteria, mold, viruses and other contaminants on the surface of the coils and drain pan.

Maintenance

ALL POWER SHOULD BE DISCONNECTED BEFORE PERFORMING MAINTENANCE OR SERVICE.

Periodic lamp replacement is required to maintain factory specification. In a commercial application the lamps should be changed after 18000 hours of operation.

Only replace with Universal UV Solutions replacement lamps to ensure safe operation. Using a non-specified lamp may damage the unit, lamp, or accessories.

REFERENCE	PART NUMBER	DESCRIPTION
1	UUVS-C-12	12" LAMP LENGTH
2	UUVS-C-18	18" LAMP LENGTH
3	UUVS-C-24	24" LAMP LENGTH
4	UUVS-C-30	30" LAMP LENGTH
5	UUVS-C-40	40" LAMP LENGTH
6	UUVS-C-50	50" LAMP LENGTH
7	UUVS-C-60	60" LAMP LENGTH
8	UUVS-C-LMP12	12" UV-C, T6 REPLACEMENT LAMP FOR UUVS-C-12
9	UUVS-C-LMP18	12" UV-C, T6 REPLACEMENT LAMP FOR UUVS-C-18
10	UUVS-C-LMP24	12" UV-C, T6 REPLACEMENT LAMP FOR UUVS-C-24
11	UUVS-C-LMP30	12" UV-C, T6 REPLACEMENT LAMP FOR UUVS-C-30
12	UUVS-C-LMP40	12" UV-C, T6 REPLACEMENT LAMP FOR UUVS-C-40
13	UUVS-C-LMP50	12" UV-C, T6 REPLACEMENT LAMP FOR UUVS-C-50
14	UUVS-C-LMP60	12" UV-C, T6 REPLACEMENT LAMP FOR UUVS-C-60

LAMP SIZE (INCHES)	INPUT VOLTAGE (V)	FREQUENCY (Hz)
18	120-277	50 / 60
24	120-277	50 / 60
30	120-277	50 / 60
40	120-277	50 / 60
50	120-277	50 / 60
60	120-277	50 / 60