



PRISM LINE 1M

Specification Sheet



5 Holt Drive,
Stony Point, NY 10980
845-947-3034
info@tslight.com

Control

- Protocol: USITT DMX-512
- DMX Channels: 4/5/6/8 or 11-channel
- Input: 3-pin XLR Male
- Output: 3-pin XLR Female
- Standalone, Master/Slave, Sound Active, Color Preset

Main Features

- 6x 25W 5-in-1 COB LEDs, 100,000 hours
- Variable electronic strobe
- Variable electronic dimmer
- Built-in color & chase macros via DMX
- Built-in automated programs + Sound Active via M/S
- RGBAW color mixing ability in standalone mode
- Beam Angle: 45 degree
- 3-pin male input and 3-pin female output
- User selectable 4/5/6/8 or 11-channel DMX modes
- Flicker-free constant-current LED driver
- Easy to use LED control panel
- PowerCon™ compatible AC power In/Out connectors

Weight & Dimensions

- 20.1" (512 mm) x 5.1" (130 mm) x 9.2 inches (232 mm)
- Weight: 11.3 lbs (5.1 kg)

Luminous Intensity

| Lux/Meter | 1 Meter | 2 Meter | 3 Meter | 4 Meter | 5 Meter |
|-----------|------------|-----------|-----------|-----------|-----------|
| Red | 4,578 Lux | 1,173 Lux | 922 Lux | 595 Lux | 440 Lux |
| Green | 7,154 Lux | 2,618 Lux | 1,365 Lux | 885 Lux | 641 Lux |
| Blue | 2,202 Lux | 783 Lux | 390 Lux | 225 Lux | 187 Lux |
| Amber | 2,513 Lux | 809 Lux | 410 Lux | 244 Lux | 179 Lux |
| White | 5,604 Lux | 1,954 Lux | 991 Lux | 615 Lux | 439 Lux |
| All | 22,447 Lux | 3,260 Lux | 4,221 Lux | 2,581 Lux | 1,694 Lux |

Mounting Options

- MNB** Clamp for pipe up to 2" OD
CM4 Canopy for mounting to J-box
USI Unistrut mount
STA Controltrac adapter (2x)

Ordering Matrix

| Model | Array | Finish - | Mounting |
|-------|-------|---------------------|-------------|
| HS5M | RGBAW | B=Black W= White | See Options |

Example: HS5-RGBAW-B-MNB

HS5M-_____-_____-_____

* Specification sheets are subject to change without notice.