



The Lenox is a soft-edged spotlight with more control over beam angle than floods, but less control than profiles. It's electronically zoomable from 12° - 65° degrees with DMX. The Lenox can accommodate barn doors for glare reduction and beam shaping. Selectable and smooth 16-bit dimming curves make it comparable with older, traditional theater fresnels. It is a perfect fit in theaters, studios or other environments that require smooth, even washes of light.

FEATURES

- 300W 2-in-1 Cool White and Warm White LED
- 3200K - 5600K Variable White
- 10,000 Total Fixture Output
- 12° - 65° Electronic Zoom
- Accepts Barndoors

CONTROL / CONNECTIONS

- DMX/RDM
- Smooth 0-100% Dimming
- 5-Pin DMX In/Out

SIZE / WEIGHT

- 16 lbs.
- Length: 17.9"
- Width: 11.5"
- Height: 8.6"

ACCESSORIES

- WINT-OMX Wireless OMX Transmitter
- WINR-DMX Wireless OMX Receiver

ELECTRIC / THERMAL

- AC 100-240V 50/60Hz
- 300W Max Power Capacity
- Working Temperature: -30 - 40°C
- 50,000 Hour LED Life

MOUNTING OPTIONS

- PC9M Theatrical Clamp 2"OD Pipe
- US1 Unistrut Adapter
- SC Heavy Duty Safety Cable

PRELIMINARY SPEC SHEET - PHOTOMETRICS, DRAWINGS, AND ADDITIONAL DATA AVAILABLE SOON.

ORDERING INFORMATION

PROJECT:	
LOCATION:	
QUANTITY:	
CONTACT:	
PHONE:	
EMAIL:	