



CT60

RGBW + Tunable White



The CT60 features tunable color and a high CRI output. It can be controlled via DMX/RDM, Lutron Ecosystem, Bluetooth, or even 010V controls. The CT60 features tunable white from 1650K-8000K with a CRI of 90+ across the entire temperature range. Rich blues, ambers, reds, violets and greens can be added in gradients or can completely saturate the output of the light. Interchangeable reflectors allow beam angles between 12° and 64°. This fixture is perfect for churches, events, or use in an architainment setting. It's also a good option for retail, due to its powerful output and high CRI values.

Manufactured in the USA - IBEW



Construction

- Steel & aluminum housing with black, white or silver finish
- 0-90° tilt, 360° rotation
- Internal multiple accessory holder
- Weight: 7 lbs.

Electrical

- Integral electronic driver
- 100-277V, 50/60Hz
- Meets FCC 47 CFR Part 15/18 Requirements
- RJ45 comes standard XLR 3-Pin and 5-Pin adapters are available.
- Consult factory when ordering canopy mount option to configure data connections.
- Can be track mounted with STA adapter and controlled with DMX or 010V protocol.
- DMX Addressing is RDM-only (No onboard DMX).

Optics


- 12°, 19°, 33° 40°, 48°, 55°, and 64° Field - changeable reflectors

Emitter 2-Year Warranty

The warranty on the LED Emitter used in this Times Square Lighting product shall have a two year warranty from the date of purchase.

*Specification sheets are subject to change without notice.

5 Holt Drive
Stony Point, NY 10980
845-947-3034
www.tslight.com



Features

- Four channel DMX mode: Dim, variable white, saturation, hue.
- Dims to below 1% of initial output
- Variable white between 1650 and 8000 kelvin. Can be controlled by 010V controller or DMX controller.

LED

- RGBW + Tunable White
- CRI: 90+ CRI
- Beam Angle: 12°, 19°, 33° 40°, 48°, 55°, 64°
- Variable white: 1650 - 8000K
- No UV or IR

CRI	Total Wattage	Lumens	Efficacy (Lm/W)
90+	60	5000	83

*Total wattage equals LED plus driver. Delivered lumen may vary depending on LED module, color temperature, optics, and accessories.

Ordering Matrix

Model	Finish	Voltage	Optics	Mounting	Dimming*
CT60	B = Black W = White S = Silver CC = Custom Color	120 277	10=10° 12=12° 19=19° 33=33° 40=40° 54=54° 64=64°	See Mounting Options	DX= DMX/RDM

Maximum ambient temperature: 35°C
Maximum operating angle: 45° from vertical


* See "Notes on Dimming" on reverse

Example: CT60-B-120-CM4-DX


CT60- _____ - _____ - _____ - _____

Photometric Data 3000° K 92 CRI


12° Spot Reflector




40° Spot Reflector




55° Medium Flood Reflector




19° Medium Flood Reflector




48° Medium Flood Reflector



33° Flood Reflector



64° Flood Reflector



Mounting Options

DT2 2-circuit track adapter for SpecTrack databus. 120V.

HDT2 Track adapter for SpecTrack 2-Circuit data track. 277V.

GAC Track adapter for 120V global pulse track.

CM4* Canopy mount (Bluetooth, 010V dimming only)

US1 6 $\frac{5}{8}$ " x 1 $\frac{1}{2}$ " Unitrut Adapter

TB8 8" x 8" Portable table base for floor and table use

MN Medium duty pipe clamp for small to large fixtures. For pipes up to 2" O.D.

PC9M Heavy duty pipe clamp for large, heavy fixtures. For pipes up to 2" O.D.

* Contact factory for wiring details.

Color Tuning Features

- Color gamut control: gradients of saturated colors from 1 - 100% can be added to color points
- 90+ CRI
- Dimmable from 100 - 1% at constant CCT
- DMX512-A-RDM or Lutron EcoSystem compatible
- DMX controls dimming, hue, saturation and tunable white
- Available with RJ45 or XLR sockets
- On-board Bluetooth Low Energy (BLE)
- Tunable range: 1650 - 8000K
- SceneSet enables up to five scenes to be preprogrammed and recalled using a 0 - 10V recommended dimmer or via Bluetooth
- Addressing and integration by RDM.
- 0-10V, DMX512-A-RDM2, Bluetooth Low Energy, Lutron® EcoSystem® are all available as control options. Must be specified and ordered to pair with desired control system from factory.
- L70 greater than 50,000 hours

Accessories

LV9	Louver
LV9BD	Louver (for use with BD9)
BD9	Barndoar
HD9	Hood
XH9	Cross Baffle Hood
CF9	Color Frame
GF9	Glass Color Filter
DF9	Dichroic Color Filter
GF9-600	5°x50° Linear Lens
GF9-601	Beam Softener
GF9-673	50°x50° Spread Lens
CCI8	Coiled Cord
SC-24	Safety Cable
W6538	RJ45 to female 5-Pin XLR Adapter

Extension Wands

SP 12	12" Stem
SP 18	18" Stem
SP 24	24" Stem
SP X	Custom Length
W6539	RJ45 to male 5-Pin XLR adapter