



LBX20

Lyra 1 x 2 Bi-Color Studio Light w/ DMX Control



5 Holt Drive
Stony Point, NY 10980
845-947-3034
tslight.com

Ikan's Lyra Studio DMX soft lights feature high-CRI chip LEDs paired with a permanently attached ½ stop soft diffusion panel, designed to provide soft, evenly diffused light. The panel is optimally positioned from the COB (chip-on-board) LEDs, creating a smooth, wrapping illumination with clean shadows. With Bi-color adjustability from 3200K to 5600K and consistent brightness across all color temperatures, these lights are versatile for any setup. The wide 110-degree beam angle ensures broad coverage, making it easy to light large areas with a single fixture.

Built for flexibility, the lights include a heavy-duty yoke and a Baby 5/8" and a Junior 1 1/8" combo pin for compatibility with various stands and studio configurations. The quick-set disk locking system provides secure positioning, while the large yellow knob at the back allows intuitive control. Users can adjust brightness, color temperature, and DMX channels with ease, aided by an LED readout for precise measurements.

The 1 x 2 LED soft panel delivers exceptionally bright, soft lighting, ideal for stage productions, talk shows, and broadcast news setups. Its user-friendly design ensures professionals have full control over their lighting environment, making it a reliable choice for any production scenario.

Special Features

- High CRI Chip LEDs paired with ½ Stop Soft Diffusion Panel
- Bi-Color Adjustable from 3200K-5600K
- Bright, Consistent Light Across all Color Temperatures
- Beam Angle of Soft Panel 110°
- Clean, Single Shadows without Artifacts
- DMX In and Out

Recommended For

- Studio Use
- Field Use

What's Included?

- 1 x Lyra Bi-Color DMX Studio Light
- 1 x Power Cord
- 1 x Power Supply
- 1 x Yoke Mount

Features

HIGH CRI CHIP LEDS

The high CRI Chip LEDs give you a strong output allowing for very bright diffused light.

BI-COLOR ADJUSTABLE

The LBX20 has a bi-color adjustable range from 3200K-5600K.

CONSISTENT LIGHT

The Lyra light gives you a very consistent bright light with all color temperatures.

110° BEAM ANGLE

A wide beam angle gives you plenty of soft light.

CLEAN SINGLE SHADOW

The single shadows give you a more natural shot.

COMBO PIN

With a Baby 5/8" and Junior 1 1/8" Combo pin allows for the use of any grip stand.

QUICK SET DISK LOCKING

The quick set disk locking system allows you to position the light when up on the grid.

SINGLE KNOB CONTROL

Users can easily adjust the brightness, color, or DMX on the fly by using the single control knob on the lights.

NEW LED READOUT SCREEN

The new, bright LED readout gives you a quick reference of the light's output.

Accessories

LEC20	Honeycomb 60° for Lyra Studio Soft Light
LEC20-30	Honeycomb 30° for Lyra 1 x 2 Studio Soft Light
LBD20	Barn Doors for Lyra 1 x 2 Studio Soft Light
PC9M	Heavy duty pipe clamp for large, heavy fixtures. For pipes up to 2" O.D.
SC	Safety Cable

Photometrics

LBX20 - Lyra Bi-Color Soft Light **3200K**

110°

FC	586	215	113	65	48	36	29	23	19	15
FEET	2'	4'	6'	8'	10'	12'	14'	16'	18'	20'

110°

LUX	5812	2432	1259	721	538	398	312	236	182	150
METERS	0.6M	1.2M	1.8M	2.4M	3M	3.6M	4.2M	4.8M	5.4M	6.1M

LBX20 - Lyra Bi-Color Soft Light **5600K**

110°

FC	652	240	127	74	54	41	32	25	20	16
FEET	2'	4'	6'	8'	10'	12'	14'	16'	18'	20'

110°

LUX	7018	2583	1367	796	581	441	344	269	215	172
METERS	0.6M	1.2M	1.8M	2.4M	3M	3.6M	4.2M	4.8M	5.4M	6.1M

Fixture Specifications

HEAD TYPE:	Bi-Color 3200K-5600K
LENS:	½ Stop Soft Diffusion
BEAM ANGLE:	110°
CONTROL / DIMMING:	DMX & Local Knob Control
BUILD MATERIAL:	Metal & Plastic Shell
COOLING SYSTEM:	Active Cooling
YOKE:	Baby 5/8" - Junior 1 1/8" Combo Pin
FIXTURE SIZE:	20" x 5" x 29" Inches
FIXTURE WEIGHT:	18 lbs.

Electrical Specifications

POWER SUPPLY:	100-220VAC (Input) 27.2VDC (Output)
POWER CONSUMPTION:	205 Watts

Shipping Specifications

SHIPPING DIMENSIONS:	26" x 7" x 31" Inches
SHIPPING WEIGHT	25 lbs.